

Dadi con rondella.

Filett. (M).....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>18</b>
Alt. x apert. chiave (HxS)...	mm	9x10	12x13	15x17	18x19	21x22	24x24	27x27
Ø rondella (D) .....	mm	14	18	22	25	28	31	34
Spessore rondella (A) .....	mm	3	3,5	4	4	4,5	5	5
<b>2829RA</b>	<b>Cad.</b>	<b>1,68</b>	<b>1,80</b>	<b>1,98</b>	<b>2,42</b>	<b>3,12</b>	<b>3,72</b>	<b>7,04</b>
Filett. (M).....	M.	<b>20</b>	<b>22</b>	<b>24</b>				
Alt. x apert. chiave (HxS)...	mm	30x30	33x32	36x36				
Ø rondella (D) .....	mm	37	40	45				
Spessore rondella (A) .....	mm	6	6	6				
<b>2829RA</b>	<b>Cad.</b>	<b>5,84</b>	<b>8,74</b>	<b>11,10</b>				

**SCU**

**2829RA**



Rondelle convesse, DIN 6319 C.

Per viti.....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>20</b>	<b>24</b>
Ø foro.....	mm	6,4	8,4	10,5	13	15	17	21	25
Ø est. x altezza.....	mm	12x2,3	17x3,2	21x4	24x4,6	28x5	30x5,3	36x6,3	44x8,2
<b>2829S</b>	<b>Cad.</b>	<b>0,84</b>	<b>0,98</b>	<b>1,14</b>	<b>1,42</b>	<b>1,68</b>	<b>2,04</b>	<b>2,38</b>	<b>3,42</b>

**SCU**

**2829S**



Rondelle larghe, DIN 6340.

Per viti.....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>18</b>
Ø foro.....	mm	6,4	8,5	10,5	13	15	17	19
Ø est. x altezza.....	mm	17x3	23x4	28x4	35x5	40x5	45x6	45x6
<b>2829T</b>	<b>Cad.</b>	<b>0,56</b>	<b>0,70</b>	<b>0,88</b>	<b>1,08</b>	<b>1,24</b>	<b>1,54</b>	<b>1,68</b>
Per viti.....	M.	<b>20</b>	<b>22</b>	<b>24</b>				
Ø foro.....	mm	21	23	25				
Ø est. x altezza.....	mm	50x6	50x8	60x8				
<b>2829T</b>	<b>Cad.</b>	<b>2,10</b>	<b>2,84</b>	<b>3,64</b>				

**SCU**

**2829T**



Rondelle normali tornite.

Per viti.....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>18</b>
Ø foro.....	mm	6,6	8,4	10,5	13	15	17	19
Ø est. x altezza.....	mm	13x3,5	18x4	22x4	28x5	35x6	35x6	40x6
<b>2829TA</b>	<b>Cad.</b>	<b>0,60</b>	<b>0,78</b>	<b>0,94</b>	<b>1,02</b>	<b>1,46</b>	<b>1,46</b>	<b>1,70</b>
Per viti.....	M.	<b>20</b>	<b>22</b>	<b>24</b>				
Ø foro.....	mm	21	23	25				
Ø est. x altezza.....	mm	40x6	45x8	45x8				
<b>2829TA</b>	<b>Cad.</b>	<b>1,80</b>	<b>2,22</b>	<b>2,30</b>				

**SCU**

**2829TA**



Rondelle concave, DIN 6319 D.

Per viti.....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>20</b>	<b>24</b>
Ø foro.....	mm	7,1	9,6	12	14,2	16,5	19	23,2	28
Ø est. x altezza.....	mm	12x2,8	17x3,5	21x4,2	24x5	28x5,6	30x6,2	36x7,5	44x9,5
<b>2829V</b>	<b>Cad.</b>	<b>0,84</b>	<b>1,00</b>	<b>1,16</b>	<b>1,44</b>	<b>1,70</b>	<b>2,04</b>	<b>2,38</b>	<b>3,42</b>

**SCU**

**2829V**



Rondelle concave, maggiorate, DIN 6319 G.

Per viti.....	M.	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>20</b>	<b>24</b>
Ø foro.....	mm	7,1	9,6	12	14,2	16,5	19	23,2	28
Ø est. x altezza.....	mm	17x4	23x4	28x5	35x5	40x5	45x6	50x8	60x10
<b>2829Z</b>	<b>Cad.</b>	<b>1,36</b>	<b>1,46</b>	<b>1,70</b>	<b>1,88</b>	<b>2,22</b>	<b>2,64</b>	<b>4,86</b>	<b>6,30</b>

**SCU**

**2829Z**



Supporti regolabili a vite. Verniciati.

Altezza max .....	mm	<b>50</b>	<b>70</b>	<b>100</b>	<b>140</b>	<b>210</b>
Altezza min .....	mm	38	54	70	100	140
Ø base x Ø piattello (Dxd) .	mm	34x34	50x50	50x50	70x65	80x70
Portata max .....	kN	20	60	60	105	180
Peso .....	Kg	0,19	0,62	0,90	2,60	4,60
<b>2830A</b>	<b>Cad.</b>	<b>29,10</b>	<b>42,60</b>	<b>64,80</b>	<b>85,20</b>	<b>162,00</b>

**SCU**

**2830A**



La misura mm 50 è priva di foro centrale.

Tipo alto. (Modello ATLAS).

Altezza max .....	mm	<b>140</b>	<b>200</b>	<b>320</b>	<b>550</b>
Altezza min .....	mm	100	140	200	320
Largh. cava di fissaggio (A)	mm	18	18	22	22
Portata max .....	kN	60	60	40	25
Peso .....	Kg	1,75	2,20	3,40	4,85
<b>2830B</b>	<b>Cad.</b>	<b>111,00</b>	<b>150,00</b>	<b>188,00</b>	<b>270,00</b>

**SCU**

**2830B**



Tutte le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Prezzi in EURO - IVA esclusa

**9**